

**Technical Data Sheet**  
**Issued, 08.04.2014**

FB 5-021 F02 Rev. 1



## DINITROL 8510

### Lacquer Spray Silver

#### **Characteristics:**

DINITROL 8510 Lacquer Spray Silver is a quick-drying acrylic lacquer with high opacity and good resistance. Based on its high pigment content, it achieves good resistance to discolouration.

#### **Areas of Application:**

The handy spray container offers specialists in the vehicle sector, as well as DIY fans, an easy-to-use product.

In addition to the vehicle sector, Lacquer Spray Silver can be used in a variety of applications in industry, the household and the garden.

#### **Method of Use:**

The substrate must be clean and free from grease, dust and rust. Old and flaky paints must be removed. Lacquer and paint residue in good condition must be matt burnished. In the case of absorptive substrates, such as wood, a pore filler must be applied beforehand in order to prevent lacquer binding agent from spreading to the substrate. A fine spray lacquer pre-coat can also be applied to seal absorptive surfaces.

Before use, shake the can (1 – 2 mins) until the mixing ball can clearly be heard. Apply the material in an even cross coat. For small surfaces, the product can also be sprayed in a circular movement. The product should be sprayed at a distance of 20 – 30 cm.

In order to prevent any blockages, hold the can downwards after use and briefly spray pure gas. Depending on temperature, humidity and coat thickness, the product is touch-dry after approx. 20 – 30 minutes.

#### **Technical data:**

Colour:	aluminium-coloured
Density:	0.75 g/cm <sup>3</sup>
Flash point:	< - 19°C
Propellant:	Propane/butane
Drying time:	approx. 20 min / 50 µm
Storage time:	24 months (between 15°C and 25°C)
Recommended working temperature:	17 – 25°C
Package size:	400 ml

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH  
Pyrmont Str. 76  
D-32676 Lügde  
Telephone:  
+49 (0) 52 81 / 9 82 98-0  
Fax:  
+49 (0) 52 81 / 9 82 98-60  
Email:  
service@dinol.com