

TECHNICAL DATA SHEET

Power Metall

LOS 362

Power Metall is an epoxy putty for quick repairs on two-component basis for aluminium, steel and other metals.

Applicable like putty. Hardens like steel in 20 minutes.

Fills holes, marks, scratches and cracks in tanks, barrels, pipes, etc. Can quickly be formed and moulded easily.

Is suitable for drilling, threading, sandblasting, sawing and can be over-painted.

It adheres to most surfaces like, metal, wood, plastic, concrete and ceramics, also at moist ground. **Power Metall** can also be used under water.

Hand consistency is achieved within 20 min., final curing after 3 h, asbestos-free.

Application

Surface to be worked on must be clean and rough. Cut off the needed material.

Kneading about 1 minute till an even coloring is reached. Apply ready putty within 2 minutes. Remove superfluous material.

Hand consistency is achieved within 20 min., final curing after 3 h, asbestos-free.

Wash hand immediately with water and soap after completion.

Technical Details:

Colour	grey
Temperature resistance:	120°C
Specific gravity:	2,18
Shrinkage:	<1 %
Work Life:	3-5 minutes
Compressive Strength:	83 N/mm ²
Full Cure Time:	60 Minuten
Shelf Stability :	min. 12 Monate

Suggestions, processing and use of our products correspond to the best knowledge at printing of this leaflet and are always given without obligation. You only can serve as a clue in consideration of the changing conditions; from this no liabilities, liability and guarantee claims can be derived. Own tests must be carried out before application. Every manufacturer of our products is liable for the retention everything legal to regulations.